



LP12-18 (12V 18Ah)

Specifications	
Rated Voltage	12
Nominal Capacity	18.0Ah (C ₂₀ , 1.75V/cell)
Dimensions	Length 182 mm
	Width 77 mm
	Container Height 168 mm Total Height 168 mm
Approx. Weight	5.4 Kg (11.9 lbs)
Terminal	T3
Layout	0
Container material	ABS
Rated Capacity (25°C)	18.0 Ah (20hr, 0.900A, 1.75V/cell)
	17.0 Ah (10hr, 1.70A, 1.75V/cell)
	15.5 Ah (5hr, 3.10A, 1.75V/cell)
	13.6 Ah (3hr, 4.52A, 1.75V/cell)
	11.2 Ah (1hr, 11.2A, 1.60V/cell)
Max. Discharge Current	270A (5s)
Internal Resistance (25°C)	Approx 16mΩ
	Discharge: -15°C ~50°C (5~122°F)
Operating Temp. Range	Charge: 0°C ~40°C (32~104°F)
	Storage: -15°C ~40°C (5~104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)
Cycle Use	Initial Charging Current less than 5.4A. Voltage 14.4V~15.0V at 25°C (77 °F)Temp. Coefficient -30mV/°C
	Initial Charging Current less than 5.4A. Voltage 13.5V~13.8V at 25°C (77 °F)Temp. Coefficient -20mV/°C
Standby Use	40°C (104°F) 103%
	25°C (77°F) 100%
	0°C (32°F) 86%
Effect Of Temp. To Capacity	LP series batteries may be stored for up to 6 months at 25°C (77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.
Self Discharge	



Description and Features

The LP Series AGM batteries have been specially developed to be widely applicable. These lead acid batteries with AGM technology are completely sealed and therefore 100% maintenance free and leak-proof. These batteries have a low self-discharge. The reliable and safe multipurpose batteries from the LP Series offer a long service life and can be used in various industries.

Features

- Absorbent Glass Mat technology
- Reliable and safe performance
- Long service life - 3-5 years in standby application (at 25°C)
- Suitable for multipurpose applications

Layout	Terminal	UL certification

Constant Current Discharge Characteristics: A (25°C)





F.V/Time	5 Min	10 Min	15 Min	20 Min	30 Min	45 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	8 Hr	10 Hr	20 Hr
1.85V/cell	49.1	33.7	26.2	21.9	16.6	12.3	10.2	7.5	6.0	4.37	3.52	3.02	2.58	2.03	1.66	0.880
1.80V/cell	52.8	35.7	27.5	22.7	17.1	12.6	10.4	7.7	6.1	4.44	3.57	3.06	2.62	2.06	1.69	0.890
1.75V/cell	55.7	37.1	28.4	23.4	17.5	12.9	10.6	7.8	6.2	4.52	3.62	3.10	2.65	2.09	1.70	0.900
1.70V/cell	58.3	38.6	29.4	24.0	18.0	13.2	10.8	8.0	6.3	4.58	3.67	3.14	2.68	2.11	1.72	0.907
1.67V/cell	60.3	39.7	30.1	24.5	18.3	13.4	11.0	8.1	6.4	4.63	3.71	3.17	2.71	2.12	1.73	0.914
1.60V/cell	64.0	41.4	31.4	25.3	18.8	13.7	11.2	8.2	6.5	4.71	3.77	3.22	2.75	2.15	1.75	0.924

Constant Power Discharge Characteristics: Wpc (25°C)

F.V/Time	5 Min	10 Min	15 Min	20 Min	30 Min	45 Min	1 Hr	1.5 Hr	2 Hr	3 Hr	4 Hr	5 Hr	6 Hr	8 Hr	10 Hr	20 Hr
1.85V/cell	93.0	64.1	50.2	42.1	32.1	23.8	19.8	14.7	11.7	8.59	6.94	5.95	5.11	4.03	3.31	1.76
1.80V/cell	99.0	67.5	52.4	43.6	32.9	24.4	20.2	15.0	11.9	8.72	7.03	6.03	5.18	4.09	3.35	1.78
1.75V/cell	103.2	69.7	53.8	44.5	33.6	24.8	20.5	15.2	12.1	8.83	7.12	6.10	5.23	4.13	3.38	1.80
1.70V/cell	107.0	72.0	55.2	45.6	34.3	25.3	20.8	15.4	12.2	8.95	7.20	6.17	5.29	4.17	3.41	1.81
1.67V/cell	109.8	73.6	56.4	46.4	34.8	25.6	21.1	15.6	12.4	9.02	7.26	6.22	5.33	4.20	3.43	1.83
1.60V/cell	114.2	75.8	57.9	47.6	35.6	26.1	21.5	15.9	12.6	9.17	7.37	6.30	5.40	4.25	3.47	1.85



LP12-18 (12V 18Ah)



Applications

- All purpose
- Uninterruptable Power Supply (UPS)
- Electric Power System (EPS)
- Emergency backup power supply
- Alarm and security system
- Communication power supply
- DC power supply
- Auto control system

General Features

- 5 years design life(25°C)
- Special exhaust structure and sealing technology, safe and reliable, flexible installation, convenient maintenance
- PbCaSn alloy for plate grids: less gassing, less self-discharging
- High quality AGM separator: extend cycle life and prevent micro short circuit
- High purity raw material: ensure low self discharge rate

Standards

- Compliance with IEC 60896 standards, EU Battery Directive
- UL, CE Certified
- UKCA Certified (for UK)
- IATF16949, ISO45001,ISO 9001 and ISO 14001 certified production facilities

(Note) All above information shall be changed without prior notice, Landport Batteries reserves the right to explain and update the latest information.